


MEGA SPEED[®]

MS190K-R10



Back Side Illuminated 4K Camera!



Saving Direct To Internal SDRAM SpeedChart - RAW Data

Min FPS: 20			Record Time In Seconds
Width*	Height	Max FPS	32GB/64GB SDRAM
4096	2176	937	4.6/9.2
3840	2176	937	6.9/13.8
2560	2176	1820	7/14
1920	1088	1820	9.9/19.8
1280	1024	1820	13/27

MS190K-R10

Rugged And Reliable

**Removable Side Panels
Allow Rapid Field repairs.
Easily Swap Out Memory,
Mother Boards, Batteries,
Drives And Any Other
Component that Gets
Damaged While In Service.**



Aerospace



Seat Ejection Testing







Distructive Testing

MEGA SPEED[®]

MS190K-R10

SAMPLE APPLICATIONS



Make Sense Of Your High Speed Image Data With The Included Mega Speed Media Player And Camera Control Software!

New Tools To Control, Measure, Synchronize, Batch Process, Clip And Compress. The Fastest Video Analysing Work-Flow Available. Helping You Make Sense Of All Your High Speed Image Data. An Outstanding Value Included With Every Mega Speed Camera.



MS190K-R10 SPECIFICATIONS

Sensor Type	4/3" CMOS sensor.
Maximum Resolution	4096 x 2176
Speed	937 fps at the maximum resolution of 4096 x 2176 pixels
	4000 fps at minimum resolution of 512x512 pixels
Pixel Size	Back side illuminated 5 um x 5 um pixel pitch.
Shutter Speed	Global electric shutter 1-2 us to 40 milli-seconds in precise 1-2 us steps for no high speed blur
On camera LCD Screen	Available as an option
Peak QE	83%
A-D Converter	10 bits
Trigger In Source	3 to 24 VDC TTL center pin positive external rising edge, switch closure or software trigger
Trigger In Modes	Pre/Post, Single Sequence, Start/Stop, Continuous Mode, Snap Shot, PIV and Autonomous Mode
Sync In/Sync Out	3.3 VDC TTL via multi pin connector center pin positive, active high
Input Voltage	14 VDC from wall adapter for battery charging or for continuous use
Frame Time Source	Internal camera time or external IRIG time for time stamping on recorded images
Data Acquisition	4 Channel Data acquisition connection of rear of camera to accept outside signal source
File Saving	User can save images in MP4, MP5, AVI, JPEG, BMP, TIFF, RAW and DNG file formats
Streaming Mode	Stream at reduced frame rates to the internal 2TB, 4TB or 8TB high speed SSD
Video Out Formats	DisplayPort interface for external monitor feed
Camera Memory	32GB or 64GB of high speed internal image buffer memory plus 2TB, 4TB or 8TB internal SSD
Removable Storage	2 Super Speed USB 3.1 ports & 1 fast micro SD UC 1 port.
Tripod Support	5, 1/4 x 20 tri-pod mounts on the bottom
PC Requirements	Windows 10 / 11. PC multiple camera control software is included
PC Software	Mega Speed Media Player for post processing, object tracking, image analysis and video editing
Gige	RJ 45 Gige port
Lens Mount	"F" mount lens mount. The "C" mount is available as an option
Camera Size	4.5" x 4.9" x 7.35"
Camera Weight	3.4 lbs with battery
Camera Body	Light weight machined anodized aluminium body
Camera Battery	Li Po re-chargeable / removable battery charges while plugged in and while in use
Temperature	-30°C to 45°C operational range. -40°C to +50°C storage range